

# ISUZU : D-Max 4WD Model

2/03 On: RA

1 of 1

	PRODUCT	FRONT	REAR	PRODUCT INFORMATION	TYPE
<b>SHOCK ABSORBERS</b>	Toughdog Gas 35mm bore	USE FOAM CELL	<b>BD1382T</b> <b>BD1388T</b> \$125 ea	35mm bore/twin tube Nitrogen Gas Charged	OE Height 45mm lift
	Toughdog Foam Cell 41mm bore	<b>FC42019B</b> <b>FC42019B</b> \$160 ea	<b>FC41382</b> <b>FC41388</b> \$160 ea	41mm bore/twin tube/60mm Casing Rebound cutoff valve	OE Height 45mm lift
	Toughdog Adjustable 40mm bore	USE FOAM CELL	<b>BM401382</b> <b>BM401388</b> \$200ea	40mm bore/twin tube/60mm casing/ 9stage adjustment	OE Height 45mm lift
<b>LEAF SPRINGS</b>	<b>Premium Pack</b> Rear: 5+2 Leaf Spring		<b>FS213</b> \$360 ea	Light Load: up to 300kg	45mm lift
	<b>Premium Pack</b> Rear: 6+2 Leaf Spring		<b>FS213H</b> \$375 ea	Medium Load: 300kg up to GVM	45mm lift
<b>TORSION BARS</b>	Toughdog	4WTB-1559  \$535 pair		27.7mm / 1039mm	All models
<b>Remember to adjust Torsion Bars after fitting Shocks.</b>					
<b>URETHANE PRODUCTS</b>	Shackle bushes		<b>TDUK-065</b>  \$95 kit	1 kit required	All models
<b>U BOLTS</b>	U Bolts must be tightened at 500km service		<b>TDUB-039</b>  \$40 kit	2 kits required	All models
<b>GREASABLE SHACKLES</b>	Shackles		<b>TDGS-386</b>  \$80 kit	1 kit required	All models

\* Warranty / Fitment sheets must be filled out when a new suspension is fitted. Failure to do so may affect warranty. \*  
Fitment sheet can be found on page 4 of this catalogue.